

BLUE GEL

SLIPPING AGENT FOR PIPE SYSTEMS WITH RUBBER SLEEVE CONNECTIONS



Ø	32	40	50	75	90	110	160	250
#	900	600	400	200	135	90	45	20

Directions for use:

1. Saw off pipes squarely, chamfer and deburr.
2. Remove dirt and moisture.
3. Apply slipping agent to pipe end and rubber sleeve.
4. Join parts immediately by sliding the tube into the sliding socket until the stopper. Properly close the container immediately after use.

Stains/residue: Remove residues with water.

TECHNICAL SPECIFICATIONS

Chemical base: Polymer

Colour: Light blue (transparent)

Viscosity: Thixotropic

Density: approx. 1 g/cm³

STORAGE CONDITIONS

Minimum of 12 months if stored in properly sealed packaging in a dry place at a temperature between +5°C and +25°C. Limited shelf life after opening.

PRODUCT DESCRIPTION

Slipping agent for assembling pipes, sleeves and fittings with rubber sleeve (sliding socket) connections in pressurised and drain systems.

FIELD OF APPLICATION

For assembling pipes, sleeves and fittings with rubber sleeve (sliding socket) connections in pressurised and drain systems. Suitable for all diameters. Also easy to apply on wet surfaces. Suitable for PVC, PVC-O, PE, PP, GRP, concrete and coated cast iron. Not suitable for ABS.

PROPERTIES

- Acid-free
- Thixotropic
- Soluble in water

QUALITY LABELS/STANDARDS

ACS: In accordance with the positive lists of ACS (Attestation de Conformité Sanitaire). Certificate IPL 12 CLP NY 037.

Belgaqua: approved for drinking water systems in accordance with Hydrocheck procedures.

KIWA: lubricants for fittings with a rubber sleeve connection. Certificate K5165 based on BRL K535

KIWA-ATA: approved for drinking water systems.

WRAS: Approved for drinking water. WRAS certificate (BS 6920).

PREPARATION

Working conditions: Do not apply at temperatures ≤ -5°C.

APPLICATION

Coverage: Indication of the number of joints per 1 L:

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.